

MIGRATION

GSI SPED SURVEY 1977

PRUDHOE BAY

SP 1-1706 LINE SP-77-22

DIRECTION NE

FIELD RECORDING DATA

SHOT INTV. 50 FEET
RECORDING FORMAT SEG-D 8058
RECORD LENGTH 10.24 SEC.
RECORDING FILTER 3 HZ TO
SAMPLE RATE 4 MILLISECONDS
NUMBER OF CHANNELS RECORDED 48
NEAR TRACE OFFSET 1000 FEET
FAR TRACE OFFSET 3475 FEET
NEAR SHOT INTERVAL 50 FT.
FAR SHOT INTERVAL 100 FT.
RECEIVER TYPE 10 GAL FLAT FISH
RECEIVER DEPTH 30 FEET
RECEIVER GROUP INTERVAL 55 FEET

SOURCE DATA

SOURCE TYPE 80 CU. IN. BOLT AIRGUN
SOURCE DEPTH 10 FEET
SOURCE PRESSURE 2000 PSI

DIGITAL PROCESSING

1 FULL MIGRATION PROCESSING
2 VELOCITY FILTER RANGE OF 5000 TO
TRACE OF 7 to 9

3 DESCRIPTION
4 TIME VARIANT FILTER
5 TIME VARIANT SPECTRAL SHAPING WITH AGC & BALANCE
6 VELOCITY ANALYSIS ON EVEN
7 NMO CORRECTION
8 TRACE MUTING
9 DIP STACK OF FOLD
10 TIME VARIANT FILTER & DEPENDING ON FULL DIP
11 TIME VARIANT SPECTRAL SHAPING
12 DIP MIGRATION
13 AGC OUTPUT
14 DISPLAY

STACK AND TIME VARIANT FILTER

WATER BOTTOM	12 TRACE
WATER BOTTOM TO 1	12 TRACE
WATER BOTTOM TO 2	8 TRACE
WATER BOTTOM TO 3	6 TRACE
	4 TRACE

TRACE 24

TRACE 1

STACK DATA

FOLD COV-OUT VELOCITY NORMAL

ALL DATA AND INFORMATION REPRODUCED ON THESE PROCESSING & INTERPRETIVE RESULTS ARE THE COPYRIGHT PROPERTY OF GEOPHYSICAL SERVICE INC. AND ARE SUBJECT TO NON-EXCLUSIVE RESTRICTIONS CONTAINED IN GSI'S MASTER SEISMIC SERVICES CONTRACT. THIS NOTICE SUPERSEDES ALL OTHER STATEMENTS

GEOPHYSICAL SERVICE INCORPORATED